

The new SB 702

Breakthrough from our SB hydraulic breaker range



Sustainable Productivity





SB BREAKER

SB702

Carrier weight class ¹⁾	t	10,0-17,0
Service weight ²⁾	kg	720
Length without working tool	mm	1012
Oil flow rate	l/min	80-120
Operating pressure	bar	120-170
Impact rate	bpm	600-1050
Working tool diameter	mm	105
Working length of working tool	mm	570
Max. hydraulic input power	kW	34
Start up mode	-	AutoStart
Sound power level guaranteed ³⁾	dB(A)	122
Sound pressure level (r=10m) ³⁾	dB(A)	94
Part number	-	8460 0300 85

1) Weights apply to standard carriers only. Any variances must be agreed with Atlas Copco and/or the carrier manufacturer prior to attachment

2) SB - Breaker with standard adapter, screw kit plus working tool

3) Important: EN ISO 3744 in accordance with directive 2000/14/EC. Full details of measurement are available in the Safety and Operating instruction of the product. It can be found on www.acprintshop.com



PART NUMBER

WORKING TOOLS LENGTH 1000 mm

WIDTH mm

3083340951	Moil point (conical)	-
3083340955	Moil point (X-profile)	-
3083340956	Chisel (cross)	105
3083340957	Chisel (X-profile)	105
3083340952	Blunt tool	-
3083340959	Wide chisel (cross)	200
3083340961	Shaft	-
3315372000	Post driver	200
3315372600	Pile driver	150
3315371200	Tamping pad	400